



SAFETY LOCK FOR SEMI-AUTOMATIC
HANDGUNS

INVENTER: Berlin Rollins
EXAMINER: Michelle Thompson

appl. #09/788,098
File date 06/04/01
DATE: 1/13/04

Listing of Claims

Claim 1 (cancelled)

Claims 1-15 (new)

SAFETY LOCK FOR SEMI-AUTOMATIC
HANDGUNS

INVENTER: Berlin Rollins
EXAMINER: Michelle Thompson

appl. #09/788,098
File date 06/04/01
DATE: 1/13/04

CLAIMS

Claims: Cancel all claims of record and substitute new claims 1 to 15 as follows on next four pages.

REMARKS- General

Applicant has rewritten all claims to define the invention more particularly and distinctly so as to overcome the technical rejection and define the invention patentable over the prior art.

Respectfully,

Berlin Rollins



SAFETY LOCK FOR SEMI-AUTOMATIC HANDGUNS

INVENTER: Berlin Rollins
EXAMINER: Michelle Thompson

appl. #09/788,098
File date 06/04/01
9/22/04

CLAIMS

I claim(new)

1.A lockable safety mechanism for use in semi-automatic hands guns ,
that will block the manual safety externally, comprising ;

A . a substantially cylindrical body having left end ,comprising a
Locking aperture formed along a substantially longitudinal axis
Of the lock core with a female receiving end formed in the left end
Of the core.

B. In a hand gun having a frame , without a hammer assembly
With a manual safety switch supported by said frame so as to
Move to and from the safe position,a spring loaded firing pin
With guide reacting when cocked to urge said firing pin to the
Firing position, a trigger mechanism carried by said frame for
Releasably holding said firing pin in the cocked position, a
Releasable lockable safety mechanism that can be carried said
Frame comprising a locking mechanism including a lock core
Movable toward and away from the manual safety switch.The
Lockable safety mechanism being engagable with said manual
Safety switch preventing it from moving to the fire position.the
Lockable safety mechanisms core being movable within its casing
For moving said core to and from the locking position, and a key
Means engageable with and disengageable from the left end of said
Lockable safety mechanism for rotating its core to and from the
Locking position.

Claim 2 (new) A hand gun as set forth in claim 1A and 1B wherein said
hand gun

can be intergrated with the right end of said lockable safety mechanism.

Claim3.(new) A hand gun as set forth in claim 1A and 1B wherein the left
end of said lockable safety mechanism and the end of said key means are
formed with complementary parts.

Claim4.(new) In a semi-automatic hand gun having a frame , a firing
mechanisms supported by said frame so as to move to and from the
cocked position, a spring within said frame acting on said firing pin

mechanism when in the cocked position to urge said mechanism to the firing position, and a trigger mechanism carried by said frame for releasably holding said firing mechanism in the cocked position, a releasable lockable safety mechanism carried by said frame comprising a lock core movable toward and away from the manual safety switch so as to hold it in a position such that the firing mechanism cannot fire, and a key means having an inner end portion engageable with and disengageable from the left end portion of said lockable safety mechanism for turning its core to and from the locked position, the left end portion of said lockable safety mechanism having spaced grooves and slots, and the right end portion of the key means having spaced projections fitting the grooves and slots in the lockable safety mechanism.

Claim5.(new) In a semi-automatic hand gun having a frame, a firing mechanism supported by said frame so as to move to and from the cocked position, a spring within said frame acting on said firing mechanism when in the cocked position to urge it into the fire position and a trigger mechanism carried by said frame for releasably holding said firing mechanism in the cocked position, releasable manual safety switch carried by said frame, comprising a manual safety switch movable from the safe to fire position, a rotatable core in the lockable safety mechanism being engagable with said safety switch so as to hold it in a position such that the hand gun cannot be fired and a key means having an inner end portion engageable with and disengageable from the left end of the lockable safety mechanisms core for turning the core from the locking position, the left end portion of said lockable safety mechanism core having spaced grooves and the inner end portion of the key having spaced projection fitting the grooves in the left end of the lockable safety mechanisms core.

Claim6.(new) In asemi-automatic hand gun having a frame, a firing mechanism supported by said frame so as to move to and from the cocked position, and a spring within said frame acting on said firing mechanism when in the cocked position to urge it to the firing position and a trigger mechanism carried by said frame for releasably holding said firing mechanism in the cocked position, a manual safety switch carried by said frame, comprising a manual safety switch movable from the safe position to the fire position, a rotatable core within a lockable safety mechanism movable into and out of locking engagement with the manual safety switch, and a key having an inner end portion engageable with and disengageable from the left end of the rotatable core of the lockable safety mechanism. The left end of said core having three spaced grooves and the inner end of the key means having complementary projections, the left end of said lockable safety mechanism core having spaces between the grooves being substantially flush with the remaining left end portion of the lockable safety mechanism to exclude from the

grooves objects having transverse blades portions extending substantially perpendicular to the axis of the locks core.

Claim7.(new) A semi-automatic hand gun as set forth in claim 6 wherein a rotatable key guide is disposed in the left end of the rotatable core , said guide having a left end wall and a outer casing therein through which the inner end of the key extends to engage the left end of the rotatable lock core disengaging the locking arms.

Claim8.(new) A semi- automatic hand gun as set forth in claim 6 , wherein the left end portion of the rotatable lock core is formed with grooves and the inner end of the key is formed with shaped prongs complementary to said grooves.

Claim9.(new) A semi-automatic hand gun as set forth in claim 6 ,wherein the left end portion of the rotatable core is formed with grooves and the inner end of the key is formed with shaped prongs complementary to said grooves , and a key guiding means adjacent to the left end of the rotatable lock core , said guiding means having an outer casing and an aperture therein through which the inner end of the key extends to engage the left end of the rotatable lock core.

Claim10.(new) In a semi-automatic hand gun having a frame , firing means including a firing pin movable within the frame when the hand gun is fired and a trigger in control of the firing means , a releasable manual safety switch for positively obstructing the movement of the firing means against operative displacement when the switch is in the safe position. A lockable safety mechanism comprising a rotatable core movable toward and away from locking engagement with the said manual safety switch, an aperture in the frame coaxially disposed with relation to the right end of the lockable safety mechanism and an actuating means for rotating the core of the lockable safety mechanism, into and out of positive locking engagement with the manual safety switch comprising a key operated through the aperture in the lockable safety mechanism to engage the left end of the rotatable core , within the lockable safety mechanism, said actuating means having provisions for preventing operation of the lockable safety mechanism by a bladed object having a straight blade end perpendicular to the axis of the rotatable core.

Claim11.(new) A semi-automatic handgun having a frame, a firing means within said frame so as to move to and from the cocked position, a spring within said frame acting on said firing means when in the cocked position to urge it to the firing position, and a trigger mechanism carried by said frame for releasably holding said firing means in the cocked position, a releasable manual safety switch for said firing means, comprising a safety switch carried by the frame and movable toward and away from said fire position, a lockable safety mechanism having a left end portion engageable with the safety switch to lock said switch against movement to the fire position, a key guide disposed in rotatable coaxial relation to the rotatable core of the lockable safety mechanism outwardly at the left end of said mechanism, a key passage through the key guide,

and a key insertable through said passage and engageable with the left end portion of the rotatable core of the lockable safety mechanism for rotating said core in to and out of locking engagement with the manual safety switch.

Claim12.(new) A semi-automatic handgun as set forth in claim 11 wherein the lockable safety mechanism has a circular-shaped left end portion.

Claim13.(new) A semi-automatic handgun as set forth in claim 11 wherein the lockable safety mechanism has a stud guide so that approximately a half rotation of the locks core is sufficient to move the core between locking and release position.

claim14.(new) A semi-automatic handgun as set forth in claim 11 where the stud guide of the locking mechanism range of movement is provided by a pin disposed in the lock outercasing generally transversed to the axis of the rotation of the locks core and intersected into the stud guide.

Claim15.(new) A semi-automatic handgun as set forth in claim 11 wherein the key guide is formed by the outercasing of the lockable safety mechanism, the said casing is secured to the lock core by a pin inserted through the stud guide and into and through the innercasing to the locks core. .